

2006

MAUMEE VALLEY POINTS RULES DIV 2

CLASSES

3500, 4500, 5500, 6500

AGE OF DRIVER

Drivers must be 14 years of age or older. Those under 18 years of age must have written parental/guardian permission.

AGE OF TRACTOR

1959 and older (any model of tractor that started in that year will be accepted)

DRAW BARS

Draw bars must not exceed 18 inches in height or less than 18 inches from center of the axle to hooking point. No part of draw bar may extend rearward beyond point of hook. Draw bars must be stationary in all directions. No clevis.

WEIGHTS

Weights must not extend rearward beyond rear tires and cannot be more than 11 feet from the center of the rear axle to the furthest point forward. No more than 12" from side of rear tire.

TIRES

No radial tires, steel wheels, or duals. Two wheel drive only. No cutting of the leading edge of the tire bar or casing allowed. Manufactured data must be intact. Tire size will be 200 sq in or less. Any rim width. No aluminum rims.

FUEL

Gas diesel or LP fuels only. No alcohol or nitrous oxide fuels may be used in tractors. Gas is allowed with a maximum specific gravity of 750. All tractors are subject to random fuel checks. Tractors manufactured to use diesel fuel only cannot be converted to LP.

RPM'S

Rpm's allowed will be determined by the Nebraska test chart. Any tractor not listed will use manufacturer's data. A 10% margin of error will be permitted. All tractors to have positive throttle stops. RPM'S will be checked randomly after hook.

SPEED LIMIT

Any gear, speed limit 3mph to be checked by radar. No shifting of TA's

CARBURETORS

Replacement carburetors allowed but with no modification of carburetor or manifold. Overhang of carburetor to manifold is not allowed. Only stock appearing manifolds are allowed. Tractors must be naturally aspirated. No turbos or blowers-except Oliver 99GM, etc. Enhanced electrical systems permitted in all classes. No rev limiters.

ENGINE, FRAMES, TRANSMISSION, REAR END, AXLE

Tractors engine must be stock or engine must be from original manufacture and must bolt in without modification using existing bell housing and motor mounts. Frames, transmission, rear end, and axle housings must be original or manufacturer's replacement. Dual exhaust not allowed except after stock manifold.

OTHER RESTRICTIONS

Oliver 88, Farmall M, Massey 44, MM-U, JD-G, Case-C/D, JD-A 1940 and up and like size tractors are not allowed in classes below 4500#. Massey 33, Oliver 77, JD-A 1939 and down and like size tractors are not allowed in classes below 4000#.

SAFETY EQUIPMENT

Wheelie bars, kill switches, all electric fuels pumps must be wired to the kill switch

**All safety equipment will be checked randomly by rules and tech committee.

****All decisions made by rule and tech committee are final.**

There is a 3 year freeze on these rules.

ALL MAUMEE VALLEY PULLERS ASSOC. GENERAL RULES APPLY